

**ADOPTION OF AN AMENDMENT TO CHAPTER 112
(ZONING) OF THE 1976 CODE OF THE COUNTY OF FAIRFAX, VIRGINIA**

At a regular meeting of the Board of Supervisors of Fairfax County, Virginia, held in the Board Auditorium, Lobby Level, Government Center Building, 12000 Government Center Parkway, Fairfax, Virginia, on Monday, March 29, 2004 the Board after having first given notice of its intention so to do, in the manner prescribed by law, adopted an amendment to Chapter 112 (Zoning) of the 1976 Code of the County of Fairfax, Virginia, said amendment so adopted being in the words and figures following, to-wit:

**BE IT ORDAINED BY THE BOARD OF SUPERVISORS OF FAIRFAX COUNTY,
VIRGINIA:**

Amend Chapter 112 (Zoning Ordinance), as follows:

Amend Article 8, Special Permits, Part 0, General Provisions, as follows :

- **Amend Sect. 8-004, Status of Special Permit Uses, by revising the introductory paragraph to Par. 4 and adding new Paragraphs 4A(6) and 4B(6) to read as follows, and renumbering the subsequent paragraphs accordingly.**
 - 4. Minor modifications to an approved special permit may be permitted when it is determined by the Zoning Administrator that such are in substantial conformance with the approved special permit and that such: are in response to issues of topography, drainage, underground utilities, structural safety, layout, design, vehicular circulation, or requirements of the Virginia Department of Transportation or Fairfax County; or are accessory uses; or are accessory structures or minor building additions as permitted by Par 4A(7) or 4B(7) below.
 - A. For approved special permits for all uses, other than churches, chapels, temples, synagogues and other such places of worship (hereinafter places of worship) and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
 - B. For approved special permits for places of worship and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
- **Amend Sect. 8-011, Submission Requirements, by revising the introductory paragraph to Par. 2 and Paragraphs 2J and 2L to read as follows:**
 - 2. Twenty-three (23) copies of a plat, including any resubmissions of the plat and supporting graphics, drawn to designated scale of not less than one inch

equals fifty feet (1" = 50'), certified by a professional engineer, land surveyor, architect or landscape architect licensed by the State of Virginia, presented on a sheet having a maximum size of 24" x 36", and one 8 ½" x 11" reduction of the plat. If the proposal cannot be accommodated on one 24" x 36" sheet at a scale of 1" = 50', a scale of not less than 1" = 100' may be used. If presented on more than one (1) sheet, match lines shall clearly indicate where the several sheets join. Such plat shall contain the following information:

J. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff from the site will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:

- (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.

- (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (2) A preliminary stormwater management narrative setting forth the following:
 - (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.
- L. Existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.

Amend Article 9, Special Exceptions, as follows:

- Amend Part 0, General Provisions, as follows:

- **Amend Sect. 9-004, Status of Special Exception Uses, by revising the introductory paragraph to Par. 4 and adding new Paragraphs 4A(6) and 4B(6) to read as follows, and renumbering the subsequent paragraphs accordingly.**

4. Minor modifications to an approved special exception may be permitted when it is determined by the Zoning Administrator that such are in substantial conformance with the approved special exception and that such: are in response to issues of topography, drainage, underground utilities, structural safety, layout, design, vehicular circulation, or requirements of the Virginia Department of Transportation or Fairfax County; or are accessory uses; or are accessory structures or minor building additions as permitted by Par. 4A(7) or 4B(7) below.
 - A. For approved special exceptions for all uses, other than churches, chapels, temples, synagogues and other such places of worship (hereinafter places of worship) and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
 - B. For approved special exceptions for places of worship and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or

- **Amend Sect. 9011, Submission Requirements, by revising the introductory paragraph to Par. 2 and Paragraphs 2J and 2L to read as follows:**

2. Twenty-three (23) copies of a plat, including any resubmissions of the plat and supporting graphics, drawn to designated scale of not less than one inch equals fifty feet (1" = 50'), certified by a professional engineer, land surveyor, architect or landscape architect licensed by the State of Virginia, presented on a sheet having a maximum size of 24" x 36", and one 8 ½" x 11" reduction of the plat. If the proposal cannot be accommodated on one 24" x 36" sheet at a scale of 1" = 50', a scale not less than 1" = 100' may be used. If presented on more than one (1)

sheet, match lines shall clearly indicate where the several sheets join. Such plat shall contain the following information:

J. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:

(1) A graphic depicting:

- (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
- (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
- (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
- (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
- (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
- (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or

stream bank stabilization measures.

- (2) A preliminary stormwater management narrative setting forth the following:
 - (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.
- L. Existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.

- **Amend Part 6, Category 6 Miscellaneous Provisions Requiring Board of Supervisors' Approval, as follows:**
 - **Amend Sect. 9-615, Provisions for a Cluster Subdivision, by revising the introductory paragraph to Par. 1 and Paragraphs 1G and 1N to read as follows:**
 1. Notwithstanding Par. 2 of Sect. 011 above, all applications shall be accompanied by twenty-three (23) copies of a plat drawn to designated scale of not less than one inch equals fifty feet (1" = 50'), certified by a professional engineer, land surveyor, architect or landscape architect licensed by the State of Virginia, presented on a sheet having a maximum size of 24" x 36", and one 8 1/2" x 11" reduction of the plat. If the proposal cannot be accommodated on one 24" x 36" sheet at a scale of 1" =

50', a scale of not less than 1" = 100' may be used. If presented on more than one (1) sheet, match lines shall clearly indicate where the several sheets join. Such plat shall contain the following information:

- G. Existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.
- N. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams, and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:
 - (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.

- (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (2) A preliminary stormwater management narrative setting forth the following:
 - (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.

- **Amend Sect. 9-622, Provisions for Modifications/Waivers/Increases and Uses in a Commercial Revitalization District, by revising the introductory paragraph to Par. 2A and Paragraphs 2A(12) and 2A(14) to read as follows:**

- 2. Notwithstanding the provisions of Par. 2 of Sect. 011 above, the plat requirements set forth below shall apply. Upon receipt of a written request with justification, the Zoning Administrator may modify or waive a plat requirement, if it is determined that the requirement is clearly not necessary for the review of the application.
 - A. Twenty-three (23) copies of a plat, including any resubmissions of the plat and supporting graphics, drawn to designated scale of not less than one

inch equals fifty feet ($1" = 50'$), certified by a professional engineer, land surveyor, architect or landscape architect licensed by the State of Virginia, presented on a sheet having a maximum size of 24" x 36", and one 8 1/2" x 11" reduction of the plat and supporting graphics. If the proposal cannot be accommodated on one 24" x 36" sheet at a scale of $1" = 50'$, a scale of not less than $1" = 100'$ may be used. If presented on more than one (1) sheet, match lines shall clearly indicate where the several sheets join. Such plat shall contain the following information:

- (12) Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams, and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:
 - (a) A graphic depicting:
 - (i) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (ii) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (iii) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (iv) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any

such road.

- (v) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
 - (vi) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (b) A preliminary stormwater management narrative setting forth the following:
- (i) Description of how the detention and best management practice requirements will be met.
 - (ii) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (iii) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (iv) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.
- (14) Existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.

Amend Article 16, Development Plans, as follows:

- **Amend Part 2, Procedures for Review and Approval of a PRC District, Sect. 16-203, PRC Plan Approval, by revising the introductory paragraph to Par. 13 and adding new Paragraphs 13A(6) and 13B(6) to read as follows, and renumbering the subsequent paragraphs accordingly.**
- 13. Minor modifications to an approved rezoning and development plan may be permitted in a PRC plan when it is determined by the Zoning Administrator that such are in substantial conformance with the approved rezoning and development plan and that such: are in response to issues of topography, drainage, underground utilities, structural safety, layout, design, vehicular circulation, or requirements of the Virginia Department of Transportation or Fairfax County; or are accessory uses; or are accessory structures or minor building additions as permitted by Par. 13A(7) or 13B(7) below.
 - A. For approved rezonings and development plans for all uses, other than churches, chapels, temples, synagogues and other such places of worship (hereinafter places of worship) and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
 - B. For approved rezonings and development plans for places of worship and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
- **Amend Part 3, Submission Requirements for a PRC District, as follows:**
 - **Amend Sect. 16-302, Development Plan, by revising Par. 3 and adding a new Par. 4L, all to read as follows:**

3. A map of the existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.
4. A plan at a scale of not less than one inch equals one hundred feet (1" = 100'), showing:
 - L. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams, and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:
 - (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
 - (f) The approximate limits of clearing and grading on-site and

off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.

- (2) A preliminary stormwater management narrative setting forth the following:
 - (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.

- **Amend Sect. 16-303, PRC Plan, by revising Par. 1O to read as follows:**

- 1. A plan at a scale of not less than one inch equals one hundred feet (1" = 100') showing:
 - O. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff from

the site will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:

- (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
 - (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (2) A preliminary stormwater management narrative setting forth the following:
 - (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best

management practice requirements.

- (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
- (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.

- **Amend Part 4, Procedures for Review and Approval of All P Districts Except the PRC District, Sect. 16-403, Site Plan/Subdivision Plat Preparation, Building Permit, Residential Use Permit and Non-Residential Use Permit, by revising the introductory paragraph to Par. 4 and adding new Paragraphs 4A(6) and 4B(6) to read as follows, and renumbering the subsequent paragraphs accordingly.**

Approval of a final development plan shall be a prerequisite and shall constitute authority for the applicant to prepare a site plan or a subdivision plat. Approval of site plans or subdivision plats and the issuance of Building Permits, Residential and/or Non-Residential Use Permits shall be in substantial conformance with the final development plan, and in accordance with the provisions of this Ordinance and Chapter 101 of The Code, The Subdivision Ordinance, and the following:

- 4. Minor modifications to an approved final development plan may be permitted when it is determined by the Zoning Administrator that such are in substantial conformance with the approved final development plan and that such: are in response to issues of topography, drainage, underground utilities, structural safety, layout, design, vehicular circulation, or requirements of the Virginia Department of Transportation or Fairfax County; or are accessory uses; or are accessory structures or minor building additions as permitted by Par. 4A(7) or 4(B)7 below.
 - A. For approved final development plans for all uses, other than churches, chapels, temples, synagogues and other such places of worship (hereinafter places of worship) and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:

- (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or

B. For approved final development plans for places of worship and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:

- (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or

- **Amend Part 5, Submission Requirements for all P Districts Except the PRC District, Sect. 16-502, Final Development Plan, by revising Par. 1Q to read as follows:**

- 1. A final plan, at a scale of not less than one inch equals one hundred feet (1" = 100'), showing:

Q. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams, and approximate water surface elevation for design storms, if applicable. In addition a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff from the site will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:

- (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.
 - (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.

- (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
 - (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (2) A preliminary stormwater management narrative setting forth the following:
- (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.
 - (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.

Amend Article 18, Administration, Amendments, Violations and Penalties, Part 2, Amendments, as follows:

- Amend Sect. 18-202, Submission Requirements, as follows:

- Revise Par. 10E and add a new Par. 10F, to read as follows, and reletter the subsequent paragraphs accordingly.

10. If the proposed amendment is for a rezoning to an R, C or I district, twenty-three (23) copies of a generalized development plan, certified by a professional engineer, architect, landscape architect or land surveyor authorized to practice as such by the State, including any resubmissions of the plan and supporting graphics, to be submitted in accordance with the provisions of Sect. 203 below, and to include the information set forth below. One 8 ½" x 11" reduction of the plan, any resubmissions and supporting graphics shall also be submitted. However, the requirement for such development plan may be modified or waived by the Zoning Administrator when it has been determined that (a) such plan is not necessary for the adequate review of the rezoning application, and (b) such development as is proposed upon rezoning is of a nature as not to have a significant adverse impact upon the community or upon the public facilities available to the property.

A generalized development plan, at a scale of not less than one inch equals one hundred feet (1" = 100'), which scale may be modified by the Zoning Administrator based on the nature and/or size of the application, shall show the following:

- E. The proposed plan for all major sanitary sewer improvements.
- F. Approximate location, estimated size of footprint in acres and type of all proposed stormwater management facilities, including the full extent of side slopes, embankments, spillways, dams, and approximate water surface elevation for design storms, if applicable. In addition, a preliminary stormwater management plan that includes information about the adequacy of downstream drainage, including the sufficiency of capacity of any storm drainage pipes and other conveyances into which stormwater runoff will be conveyed. When there is 2500 square feet or more of land disturbing activity on the entire application property, in addition to the above, the preliminary stormwater management plan shall include:
 - (1) A graphic depicting:
 - (a) The approximate footprint of the stormwater management

facility and, where applicable, the height of the dam embankment and the location of the emergency spillway outlet for each stormwater management facility.

- (b) The approximate on-site and off-site areas to be served by each stormwater management facility, along with the acreage draining to each facility.
 - (c) A preliminary layout of all on-site drainage channels, outfalls and pipes, including inlet and outlet pipes within the stormwater management facility.
 - (d) The approximate location or alternative locations, if any, of any maintenance access road or other means of access to the stormwater management facility, and the identification of the types of surfaces to be used for any such road.
 - (e) Proposed landscaping and tree preservation areas in and near the stormwater management facility.
 - (f) The approximate limits of clearing and grading on-site and off-site for the stormwater management facility, storm drainage pipes, spillways, access roads and outfalls, including the provision of energy dissipation, storm drain outlet protection and/or stream bank stabilization measures.
- (2) A preliminary stormwater management narrative setting forth the following:
- (a) Description of how the detention and best management practice requirements will be met.
 - (b) The estimated area and volume of storage of the stormwater management facility to meet stormwater detention and best management practice requirements.
 - (c) For each watercourse into which drainage from the property is discharged, a description of the existing outfall conditions, including any existing ponds or structures in the outfall area. The outfall area shall include all land located between the point of discharge from the property that is

located farthest upstream, down to the point where the drainage area of the receiving watercourse exceeds 100 times the area of that portion of the property that drains to it or to a floodplain that drains an area of at least 1 square mile, whichever comes first.

- (d) Description of how the adequate outfall requirements of the Public Facilities Manual will be satisfied.

- **Revise relettered Par. 10I to read as follows:**

- 10. If the proposed amendment is for a rezoning to an R, C or I district, twenty-three (23) copies of a generalized development plan, certified by a professional engineer, architect, landscape architect or land surveyor authorized to practice as such by the State, including any resubmissions of the plan and supporting graphics, to be submitted in accordance with the provisions of Sect. 203 below, and to include the information set forth below. One 8 ½" x 11" reduction of the plan, any resubmissions and supporting graphics shall also be submitted. However, the requirement for such development plan may be modified or waived by the Zoning Administrator when it has been determined that (a) such plan is not necessary for the adequate review of the rezoning application, and (b) such development as is proposed upon rezoning is of a nature as not to have a significant adverse impact upon the community or upon the public facilities available to the property.

A generalized development plan, at a scale of not less than one inch equals one hundred feet (1" = 100'), which scale may be modified by the Zoning Administrator based on the nature and/or size of the application, shall show the following:

- I. Existing topography with a maximum contour interval of two (2) feet and a statement indicating whether it is air survey or field run.

- **Amend, Sect. 18-204, Proffered Condition Regulations, by revising the introductory paragraph to Par. 5 and adding new Paragraphs 5A(6) and 5B(6) to read as follows, and renumbering the subsequent paragraphs accordingly.**

- 5. Notwithstanding the provisions of Part 4 of Article 1, minor modifications to the proffered conditions may be permitted when it is determined by the Zoning Administrator that such are in substantial conformance with the proffered conditions and that such are in response to issues of topography, drainage, underground utilities, structural safety, layout, design, vehicular circulation, or requirements of the Virginia Department of Transportation or Fairfax County; or are accessory uses; or are accessory structures or minor building additions as permitted by Par 5A(7) or 5B(7) below.

- A. For proffered rezonings for all uses, other than churches, chapels, temples, synagogues and other such places of worship (hereinafter places of worship) and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or
- B. For proffered rezonings for places of worship and places of worship with a child care center, nursery school or private school of general or special education, the modifications shall, in no event:
 - (6) Result in an increase in the amount of clearing and/or grading for a stormwater management facility, including any clearing and/or grading associated with spillways, inlets, outfall pipes or maintenance roads, that reduces non-stormwater management open space, tree save and/or landscaping area on the lot; or

Amend Article 20, Ordinance Structure, Interpretations and Definitions, Part 1, Ordinance Structure, Sect. 20-105, Paragraphs, to read as follows:

For purposes of further organization, each Section may be subdivided into Paragraphs which are represented by such numbers as 1, 2, 3; which may be further subdivided as A, B, C...(1), (2), (3)... (a), (b), (c)...and (i), (ii), (iii)...

This amendment shall become effective on July 1, 2004 at 12:01 a.m.

GIVEN under my hand this 30th day of March, 2004.

NANCY VEHR
Clerk to the Board of Supervisors